



Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	Viega GmbH & Co. KG
Address	Viega Platz 1, Attendorn, 57439, Germany
Place of Production	Viega GmbH & Co. KG Viega Strasse 1, Großheringen, 99518, Germany
Type	Compression Fittings
Description	Megapress is a black steel piping system with SC-feature. The SC feature enables to quickly identify unpressed fittings. The press connection is performed by a special press tool. The fittings are offered with EPDM, HNBR and FKM sealing element.
Trade Name	Viega Megapress, Viega Megapress G, Viega Megapress S, Viega Megapress S XL
Application	As piping components in Class III - piping systems on ships classed or intended for Classification with Lloyd's Register. <u>Restrictions:</u> <ol style="list-style-type: none">1. Starting/control air and CO2 systems.2. Inside machinery spaces of category A, accommodation spaces or cargo pump rooms for main or distribution lines of inert gas systems.3. Fire main, water spray or sprinkler systems which are not always filled with water.4. Bilge lines in high fire risk compartments5. Scupper pipes below freeboard deck overboard6. EPDM sealing is not suitable for most of oily fluids

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Torsten Schroeder

Engineering - Piping - Senior Specialist to
Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



Type Approval Certificate

Specified Standard	IACS P 2.11 including wet fire endurance test, LR Rules and Regulations for the Classification of Ships, 2023.
Other Conditions	For deck and bulkhead penetrations see also the requirements of the National Authorities. Selection and installation to be in accordance with the producer's instructions and recommendations.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR21315481TA / (14/20020(E4))

The Design Appraisal Document HTS/ENS 30687-14, Issue No. 6 and its supplementary Type Approval Terms and Conditions form part of this Certificate.

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



Appendix

RATINGS

Dimensions: DN 10 to DN 100 (incl. 38, 44.5 and 57 mm)
MAWP: 1,6 MPa, (232 psi)
Vacuum lines 170 mbar absolute

Sealing materials	EPDM	HNBR	FKM
Size range	3/8" up to 2" (incl. 38, 44.5 and 57 mm) DN10 to DN50	1/2" up to 2" DN15 to DN50	3/8" up to 4" DN10 to DN100
Temperature range	-10 to +110°C 14 to 230°F	-40 to +82°C -40 to 180°F	-5 to +140°C 23 to 284°F