

Tech Data

Viega ProPress® 3-Way Valve Model 2976.3



Description

Viega ProPress 3-way mixing valve helps regulate system fluid temperatures by mixing fluids from two sources. The valve is ideal for controlling temperatures in heating, cooling, and radiant

application. The valve can be controlled both manually or through the use of an actuator (Model #2877.10).

Features

- Female BSP threads
- Delivered with 3 ProPress tailpieces with EPDM sealing elements
- EPDM flat gasket

Ratings

- Temperature range: 0°F - 250°F
- Max. Operating Pressure: 250 psi




This document is subject to updates. For the most current Viega technical literature, please visit www.viega.us.



Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. **Installation by non-professionals may void Viega LLC's warranty.**

Component	Material
Body	Bronze
Stem	Stainless Steel
Insert	Brass
Seal	EPDM
Cap	Plastic

Viega ProPress 3-Way Valve - Model 2976.3



Part No.	Size (in)	A1 (in)	A2 (in)	A3 (in)	L1 (in)	L2 (in)	L3 (in)	L4 (in)	Cv (US gal/min)
	1								
87420	1/2	1.85	1.85	2.56	2.68	2.68	2.87	1.65	2.89
87425	3/4	2.28	2.28	2.72	3.19	3.19	3.47	2.09	5.09
87430	1	2.52	2.52	2.87	3.43	3.43	3.62	2.09	6.59
87435	1 1/4	2.68	2.68	2.99	3.70	3.70	3.86	2.09	8.32
87440	1 1/2	3.07	3.07	3.07	4.49	4.49	4.65	2.13	9.83
87445	2	3.07	3.07	3.31	4.65	4.65	4.72	2.32	11.56



Viega LLC
585 Interlocken Blvd.
Broomfield, CO 80021

Phone (800) 976-9819
www.viega.us

TD-PP 0424 ProPress 3-Way Valve

viega