Tech Data

Viega ProPress® Bronze 3-Piece Ball Valve, Model 2972.1ZL



The ProPress Bronze 3-Piece Ball valve is equipped with a full port, stainless-steel 3-piece body. The ball valve features an EPDM sealing element and Viega's Smart Connect® Technology

for easy identification of unpressed connections during pressure testing.

Features

- 316 stainless steel ball
- Blowout-proof 316 stainless steel stem
- Adjustable packing nut
- Reinforced PTFE seats
- ProPress connection
- Smart Connect technology

Accessories

- Handle, Model 4875,80
- Stem Extension, Model 2972.12

Approvals

- NSF_®-61-372
- NSF_®-U.P. Code
- IAPMO/ANSI Z1157
- Listed by NSF to Commercial Hot



This document is subject to updates. For the most current Viega technical literature, please visit www.viega.us.

Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by nonprofessionals may void Viega LLC's warranty.




Zero Lead identifies Viega products meeting the lead free requirements of NSF/ANSI/CAN 61 through testing under NSF/ANSI/CAN 372 (0.25% or less maximum weighted average lead content).

Ratings

- 250 CWP
- Temperature Range: 0°F 250°F ■ Max. Operating Pressure: 250 psi

Component	Material			
Body	316 Stainless Steel			
Ball	316 Stainless Steel			
Seat	Reinforced PTFE			
Stem	316 Stainless Steel			
Nut	316 Stainless Steel			
Sealing Element	EPDM			

Viega ProPress Ball Valve Zero Lead Bronze 3-Piece - Model 2972.1ZL



Part No.	Size (in)	H1 (in)	H2 (in)	L1 (in)	L2 (in)	A1 (in)	Cv (US gal/min)	Bolt Torque (ft/lbs)
87275	1/2	2.28	0.91	1.93	3.98	1.10	10.9	7.5
87280	3/4	2.83	1.06	2.52	5.87	1.61	23.9	15
87285	1	2.91	1.14	2.60	5.87	1.70	47.3	15
87290	11/4	3.35	1.38	3.27	7.56	2.24	76.4	22.5
87295	1½	3.58	1.54	3.78	7.56	2.36	113	22.5
87300	2	3.90	1.81	4.06	7.56	2.48	210	22.5



Phone (800) 976-9819 www.viega.us

